MULE PRO-FXT™ 1000 LE RANCH EDITION







POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (L,H,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 90 amp

(max)

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

Dimensions (LxWxH) person)

Cargo Bed Load Capacity

Payload Capacity

1,616.3 lb / 1,263.5 lb CA Model

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2,000 l

Lighting (2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 135.8 in

Overall Width 64.0 in

Overall Height 80.9 in

Curb Weight 1,966.9 lb* / 1,969.1 lb* CA Model

Wheelbase 92.3 i

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Wheel Type Alloy

Additional Features Roof, Additional Front Cup Holders, WARN® VRX 45 Winch,

Premium Seats, Self-Leveling Rear Suspension

Color Choices Metallic Titanium

Warranty Kawasaki STRONG 3-Year Limited Warranty

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/11.0 in

Rear Suspension / Wheel Travel Double wishbone/10.1 in

Front Tires

26 x 9.00-12, radial 26 x 11.00-12, radial

Rear Tires Steering

Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Ground Clearance

12.6 in (max), 11.6 in (std)



