## JET SKI® STX® 160









## **POWER**

4-stroke, DOHC, four valves per cylinder, 4-**Engine** 

cylinder inline

**Displacement** 1,498cc

**Bore x Stroke** 83.0 x 69.2mm

Compression

Ratio

10.6:1

Induction Naturally aspirated

**Maximum Boost** N/A

**Cooling System** Inducted water

DFI® with 60mm throttle body **Fuel System** 

Ignition TCBI with digital advance

**Starting System** Electric

**Propulsion** 

**System** 

148mm jet pump, axial-flow, single stage

**Impeller** 3-blade, oval-edge stainless steel **Thrust** 957 lb

## **PERFORMANCE**

Lubrication Semi-dry sump system

Coupling Direct drive from engine

**Oil Capacity** 5.8 qt.

**Fuel Capacity** 20.6 gal.

**Load Capacity** 496 lb.

Storage 35.0 gal. **Capacity** 

## **DETAILS**

**Overall Length** 124.1 in

**Overall Width** 46.5 in.

**Overall Height** 45.4 in.

**Curb Weight** 864.4 lb\*

3

Seating

**Capacity** 

**Color Choices** Crystal White/Pearl Neon Yellow

12 Month Limited Warranty Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski® watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.