
VULCAN® 900 CUSTOM









Single 300mm hydraulic disc

Single 270mm hydraulic disc

POWER

Engine 4-stroke, 55-degree V-twin, liquid-cooled

Displacement 903cc/55.10 cu in

Bore x Stroke 88.0 x 74.2mm

Compression

Ratio

9.5:1

Maximum

Fuel System

58.2 lb-ft @ 3,500 rpm

Torque

DFI® with 34mm throttle bodies (2), with

sub-throttle valves

Ignition TCBI with Electronic Advance

Transmission 5-speed with positive neutral finder

Final Drive Kevlar-reinforced belt

DETAILS

Front Brakes

Rear Brakes

Front Tire

Rear Tire

Frame Type Semi-double cradle, high-tensile steel

80/90-21

180/70-15

Rake/Trail 33°/7.2 in

Overall Length 94.7 in

Overall Width 35.2 in

Overall Height 44.1 in

Ground 5.5 in Clearance

Seat Height 27.0 in

Curb Weight 610.8 lb*

Fuel Capacity 5.3 gal

Wheelbase 64.8 in

Color Choices Metallic Matte Dark Gray/Metallic Flat

Spark Black

Warranty 12 Month Limited Warranty

PERFORMANCE

Front
Suspension /
Wheel Travel

Danie

Rear Suspension / Wheel Travel Uni-Trak® swingarm, 7-way adjustable

41mm Showa telescopic fork/5.9 in

spring preload/4.1 in

Scan with camera to view videos, key features and more.

