## 2024 **BRUTE FORCE® 750**









Engine	4-stroke, V-twin, SOHC, liquid-cooled	
Displacement	749cc	
Bore x Stroke	85.0 x 66.0mm	
<b>Compression Ratio</b>	9.3:1	
Maximum Torque	42.7 lb-ft @ 4750 rpm	
Fuel System	DFI® with two 36mm throttle bodies	
Ignition	Digital DC-CDI	
Transmission	Automatic CVT (H,L,N,R)	
Final Drive	Selectable 2WD/4WD with variable control front differential lock, shaft	

Steering	Rack-and-pinion
Electronic Power Steering (EPS)	Yes
Turning Radius	10.5 ft
Towing Capacity	1,250 lb
Total Rack Capacity	264.5 lb
Rack Capacity, Front/ Rear	88.0/176.0 lb
Lighting	All-LED lighting

## DETAILS

rential	Frame Type	Double-cradle, high-tensile tubular steel
	Tread Width	37.0/35.6 in
	Overall Length	86.0 in
	Overall Width	46.1 in
	Overall Height	47.6 in
	Seat Height	35.2 in
	Curb Weight	707.8 lb*
	Wheelbase	50.6 in
brake	Instruments	Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, and battery voltage)
	Special Features	Full-color TFT Instrumentation, KQR™ system
	Color Choices	Timberline Green
	Warranty	12 Month Limited Warranty

## **CAPABILITY**

Front Suspension / Wheel Travel	Double wishbone, adjustable spring preload/6.9 in
Rear Suspension / Wheel Travel	Double wishbone, adjustable spring preload/7.4 in
Front Tires	AT 25 x 8-12
Rear Tires	AT 25 x 10-12
Front Brakes	Dual hydraulic 176mm discs with 2-piston calipers
Rear Brakes	Sealed, oil-bathed, multi-disc with independent park brake
Ground Clearance	9.0 in/9.6 in (max preload)
Starting System	Electric
Fuel Capacity	5.0 gal

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.