BRUTE FORCE® 750 LE EPS CAMO







D	n	١	M	Г	D
г	u	ľ	N	E	π

Engine 4-stroke, V-twin, SOHC, liquid-cooled

Displacement 749c

Bore x Stroke 85.0 x 66.0mm

Compression Ratio 9.3:1

Maximum Torque 42.7 lb-ft @ 4750 rpm

Fuel System DFI® with two 36mm throttle bodies

Ignition Digital DC-CDI

Transmission Automatic CVT (H,L,N,R)

Final Drive Selectable 2WD/4WD with variable control front differential

lock, shaft

CAPABILITY

Front Suspension / Double wishbone, adjustable spring preload/6.9 in Wheel Travel

Rear Suspension / Wheel Travel

Double wishbone, adjustable spring preload/7.4 in

Front Tires

AT 25 x 8-12

Rear Tires AT 25 x 10-12

Front Brakes Dual hydraulic 176mm discs with 2-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc with independent park brake

Ground Clearance 9.0 in/9.6 in (max preload)

Starting System Electric

Fuel Capacity 5.0 gal

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Electronic Power Yes

Turning Radius 10.5 ft

Towing Capacity 1,250 lb

Rack Capacity, Front/ 88.0/176.0 lb

Rear

Lighting All-LED lighting

DETAILS

Total Rack Capacity

Frame Type Double-cradle, high-tensile tubular steel

264.5 lb

Tread Width 37.0/35.6 in

Overall Length 86.0 in

Overall Width 46.1 in

Overall Height 47.6 in

Seat Height 35.2 in

Curb Weight 732.1 lb*

Wheelbase 50.6 in

Instruments Digital speedometer, 2WD/4WD drive indicator, fuel gauge,

odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and

battery voltage)

Special Features Full-color TFT Instrumentation, KQR™ system

Color Choices TRUETIMBER® STRATA

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.