

2024

KLX[®] 230R

Kawasaki
Let the Good Times Roll[®]



POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Fuel System	DFI [®] with 32mm Keihin throttle body
Ignition	TCBI Electronic Advance
Transmission	6-speed, return shift with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	100/100-18
Front Brakes	Single 240mm petal disc with a dual-piston caliper
Rear Brakes	Single 220mm petal disc with single-piston caliper

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/9.8 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with adjustable spring preload/9.9 in
Front Tire	80/100-21

DETAILS

Frame Type	High-tensile steel, box-section perimeter
Rake/Trail	26.5° / 4.4 in
Overall Length	80.5 in
Overall Width	33.1 in
Overall Height	47.2 in
Ground Clearance	11.8 in
Seat Height	36.4 in
Curb Weight	253.6 lb* / 262.3 lb* CA Model
Fuel Capacity	1.7 gal
Wheelbase	53.5 in
Color Choices	Lime Green, Battle Gray
Warranty	6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.