## **KLX®230 S**









## **POWER**

**Engine** 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

9.4:1

Compression

Ratio

Maximum Torque 13.2 lb-ft @ 6,400 rpm

Fuel System

DFI® with 32mm throttle body

Ignition

TCBI with Electronic Advance

**Transmission** 

6-speed

**Final Drive** 

Sealed chain

**Electronic Rider** 

Aids

Anti-lock Brake System (ABS)

## **PERFORMANCE**

Front
Suspension /
Wheel Travel

Rear Suspension
/ Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.7 in

Front Tire

2.75 x 21

Front Brakes Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)

**Rear Brakes** Single 220mm petal disc with single-piston

caliper (and ABS)

## **DETAILS**

Frame Type Perimeter, high-tensile steel

Rake/Trail 24.6°/3.7 in

Overall Length 81.8 in

Overall Width 33.2 in

Overall Height 44.8 in

Ground 9.4 in

Clearance

Seat Height 33.2 in

Curb Weight 291.0/293.2 lb\* 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Special Features | ERGO-FIT®, LCD Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

**Color Choices** Lime Green, Battle Gray

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.

**Rear Tire** 



4.10 x 18