## <sup>2024</sup> KLX<sup>®</sup>230SM ABS







## **Front Brakes** Single 300mm petal disc with a dual-piston **POWER** caliper and ABS **Rear Brakes** Single 220mm petal disc with single-piston Engine 4-stroke single, SOHC, air-cooled caliper and ABS Displacement 233cc DETAILS Bore x Stroke 67.0 x 66.0mm Compression 9.4:1 Perimeter, high-tensile steel Frame Type Ratio 24.9°/3.0 in Rake/Trail Maximum 13.2 lb-ft @ 6,400 rpm **Torque Overall Length** 80.1 in DFI® with dual 32mm throttle bodies **Fuel System Overall Width** 33.2 in TCBI with Electronic Advance Ignition 44.2 in **Overall Height** Transmission 6-speed 8.6 in Ground Clearance **Final Drive** Sealed chain **Seat Height** 33.0 in **Electronic Rider** Anti-lock Brake System (ABS) Aids **Curb Weight** 299.8/302.0 lb\* 50-State Model

## PERFORMANCE

Front Suspension / Wheel Travel	37mm inverted fork/7.4 in	Specia
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/8.7 in	Color (
Front Tire	110/70-17	Warra
Rear Tire	120/70-17	

Ground<br/>Clearance8.6 inSeat Height33.0 inCurb Weight299.8/302.0 lb\* 50-State ModelFuel Capacity2.0 galWheelbase53.7 inSpecial FeaturesERGO-FIT®, LCD Instrumentation with<br/>Smartphone Connectivity via RIDEOLOGY THE<br/>APP MOTORCYCLEColor ChoicesBattle GrayWarranty12 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.