





D	N	V	M	C	D
Г	U	ľ	V	C	П

2-stroke single with exhaust power valve (KIPS), liquid-cooled

Displacement 84cc

Bore x Stroke 48.5 x 45.8mm

Compression Ratio 10.9:1 (low speed) / 9.0:1 (high speed)

Fuel System

28mm Keihin carburetor

Ignition

CDI with Digital Advance

Transmission

6-speed, return shift, with wet multi-disc

manual clutch

Final Drive

Chain

PERFORMANCE

Front
Suspension /
Wheel Travel

36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / Wheel Travel Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in

Front Tire

70/100-17

Rear Tire 90/100-14

Front Brakes Single 220mm petal disc with dual-piston caliper

Rear Brakes Single 184mm petal disc with single-piston caliper

DETAILS

Frame Type	High-tensile steel perimeter design with subframe member
Rake/Trail	29°/3.8 in
Overall Length	72.0 in
Overall Width	30.1 in
Overall Height	43.3 in
Ground Clearance	11.4 in
Seat Height	32.7 in
Curb Weight	164.4 lb*
Fuel Capacity	1.32 gal
Wheelbase	49.8 in
Color Choices	Lime Green

Not Available





Warranty