MULE[™] 4010 4x4 FE







| D | N | V | V | C | D |
|---|---|---|---|---|---|
| Г | u | ľ | V | Г | ĸ |

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 2.99 x 2.68 in

Compression Ratio

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive

(max)

Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

23 amp

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in **Wheel Travel**

Rear Suspension / **Wheel Travel**

DeDion Axle/2.8 in

Front Tires

23x11.00-10

Rear Tires 23x11.00-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type

Independent, Mechanical Drum

Front Brakes

Drum

Rear Brakes Drum **Ground Clearance** 6.9 in

Fuel Capacity 6.3 gal

Turning Radius 11.2 ft

Cargo Bed 46.3 x 51.6 x 11.4 in

Dimensions (LxWxH)

Cargo Bed Load 800 lb

Capacity

Payload Capacity 1,312 lb

Seating Capacity

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

DETAILS

Overall Length 116.7 in

Overall Width 62.0 in

Overall Height 78.1 in

Curb Weight 1,448.7 lb*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature

warning light, horn, 12V DC outlet, fuel gauge, hour

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White

Kawasaki STRONG 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.

