## **MULE™ 4010 TRANS4x4® FE**







## **POWER**

**Engine** 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

**Bore x Stroke** 2.99 x 2.68 in

Compression Ratio 10:3:

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking N

**Alternator Output** 

(max)

23 amp

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel

**Rear Tires** 

DeDion Axle/2.8 in

23x11.00-10

Front Tires 23x11.00-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type

Independent, Mechanical Drum

Front Brakes Drum

Rear Brakes Drum

Ground Clearance 7.7 in

Turning Radius 12.8 ft

Cargo Bed 50.4 x 47.6 x 11.2 in (2-person) 30.3 x 47.6 x 11.2 in (4-

800 lb (2-person) 401 lb (4-person)

Dimensions (LxWxH)

Cargo Bed Load

**Fuel Capacity** 

Capacity

Payload Capacity 1,330 lb

Seating Capacity 2-4

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

6.3 gal

## **DETAILS**

Overall Length 128.5 in

Overall Width 58.5 in

Overall Height 78.1 in

Curb Weight 1,614.1 lb\*

Wheelbase 85.2 in

**Instruments** Parking brake warning light, coolant temperature

warning light, horn, 12V DC outlet, fuel gauge, hour

meter

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

**Color Choices** Bright White

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

