MULE PRO-DXT™ FE DIESEL EPS







POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2,400 rpm

Bore x Stroke 2.91 x 3.03 in

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

Ground Clearance 10.2 in

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed

Dimensions (LxWxH)

999 lb (3-person) / 350 lb (6-person)

Cargo Bed Load

Capacity

1,574 lb

person)

Payload Capacity

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights.

55 amp

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Rear Suspension / **Wheel Travel**

Double wishbone/8.5 in (L) /8.7 in (R)

Front Tires 26 x 9.00-12 **Rear Tires** 26 x 11.00-12

Electric Power Steering (EPS), Tilt steering Steering

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 79.5 in

Curb Weight 1,971.3 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

