2024

MULE SX™









POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 20.6 lb-ft @ 2,200 rpm

Bore x Stroke 3.23 x 2.99 in

Compression Ratio 8.3:1

Fuel System Nikki 6C1026 carburetor

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking No

Alternator Output 17 amp

(max)

Rear Brakes Drum **Ground Clearance** 6.1 in **Fuel Capacity** 4.2 gal **Turning Radius** 10.8 ft

Cargo Bed Dimensions

DETAILS

Overall Length

Overall Width

Overall Height

35.6 x 40.9 x 9.6 in

(LxWxH)

Cargo Bed Load Capacity

399 lb

106.7 in

52.6 in

70.1 in

Payload Capacity 926 lb **Seating Capacity**

Towing Capacity 1,100 lb**

Lighting (2) Halogen headlights, tail/brake lights

CAPABILITY

MacPherson Strut/3.1 in Front Suspension / **Wheel Travel**

Rear Suspension /

Unit Swingarm/3.1 in

Wheel Travel

Front Tires 22x9.00-10 **Rear Tires** 22x11.00-10

Steering Rack-and-pinion

Park Brake Type

Independent, Mechanical Drum

Front Brakes Drum

**Requires Optional Hitch

Scan with camera to view videos, key features and more.



Curb Weight 967.6 lb* Wheelbase 70.1 in Instruments Fuel gauge, hour meter, oil temp light, parking brake **Color Choices** Dark Royal Red, Timberline Green Warranty Kawasaki STRONG 3-Year Limited Warranty