MULE SX™ 4x4









POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2,400 rpm

Bore x Stroke 3.23 x 2.99 in

Compression Ratio

Fuel System Fuel Injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking No

Alternator Output

(max)

Rear Brakes Drum **Ground Clearance** 6.7 in **Fuel Capacity** 4.2 gal **Turning Radius** 10.8 ft 35.6 x 40.9 x 9.6 in

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load 399 lb

Capacity

915 lb

Seating Capacity

Payload Capacity

Towing Capacity 1,100 lb**

Lighting (2) Halogen headlights, tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.1 in **Wheel Travel**

22.9 amp

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires

24x9.00-10

Rear Tires 24x11.00-10

Steering Rack-and-pinion

Park Brake Type

Independent, Mechanical Drum

Front Brakes Drum

DETAILS

Curb Weight

Warranty

Overall Length 106.7 in **Overall Width** 52.6 in

Overall Height 70.9 in

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

Color Choices Dark Royal Red, Timberline Green

1,031.9 lb*

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

