2024

NINJA® 500







METALLIC SPARK BLACK/METALLIC FLAT RAW GRAYSTONE



METALLIC MATTE WHITISH SILVER/METALLIC MOONDUST GRAY



PASSION RED/METALLIC FLAT SPARK BLACK/ METALLIC MATTE DARK GRAY



POWER

Engine 4-stroke, Parallel Twin, DOHC, liquid-cooled

51.0 hp1 @ 10,000 rpm

31.7 lb-ft @ 7,500 rpm

TCBI with Digital Advance

Displacement 451cc

Bore x Stroke 70.0 x 58.6mm

Compression Ratio

Maximum Horsepower

Maximum Torque

Fuel System

Ignition

Transmission

Final Drive

6-speed

Sealed chain

11.3:1

Electronic Rider

Rear Brakes

Single 220mm disc with single-piston caliper (and ABS)

DETAILS

Frame Type Trellis, high-tensile steel

Rake/Trail 24.5°/3.6 in

Overall Length 78.5 in

Overall Width 28.7 in

Overall Height 44.1 in

Ground Clearance 5.7 in

Seat Height 30.9 in

Dry Weight 344.0 lb** (ABS) / 346.2 lb** (ABS) 50-State Model,

339.6 lb** (non-ABS) / 341.8 lb** (non-ABS) 50-State

Curb Weight 374.9 lb*(ABS) / 377.1 lb* (ABS) 50-State Model, 370.4 lb* (non-ABS) / 372.6 lb* (non-ABS) 50-State Model

Fuel Capacity 3.7 gal

54.1 in Wheelbase

Color Choices

Special Features ERGO-FIT®, LCD Instrumentation with Smartphone

Connectivity via RIDEOLOGY THE APP

Metallic Spark Black/Metallic Flat Raw Graystone, Metallic Matte Whitish Silver/Metallic Moondust Gray, Passion Red/Metallic Flat Spark Black/Metallic Matte

Dark Gray

Warranty 12 Month Limited Warranty

PERFORMANCE

Front Suspension / **Wheel Travel**

41mm hydraulic telescopic fork/4.7 in

DFI® with dual 32mm throttle bodies

Rear Suspension / **Wheel Travel**

Horizontal back-link with adjustable spring

Economical Riding Indicator, Anti-lock Brake System

preload/5.1 in

Front Tire

110/70-17

Rear Tire

150/60-17

Front Brakes

Single 310mm semi-floating disc with 2-piston

Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.

calipers (and ABS)

Scan with camera to view videos, key features and more.



'Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.