

2024

NINJA[®] 500 SE ABS

Kawasaki

Let the Good Times Roll[®]



PASSION RED/METALLIC FLAT SPARK BLACK/
METALLIC MATTE DARK GRAY



| POWER | | Front Brakes | Single 310mm semi-floating disc with 2-piston calipers and ABS |
|---------------------------------|--|------------------|---|
| Engine | 4-stroke, Parallel Twin, DOHC, liquid-cooled | Rear Brakes | Single 220mm disc with single-piston caliper and ABS |
| Displacement | 451cc | DETAILS | |
| Bore x Stroke | 70.0 x 58.6mm | Frame Type | Trellis, high-tensile steel |
| Compression Ratio | 11.3:1 | Rake/Trail | 24.7° /3.6 in |
| Maximum Horsepower | 51.0 hp ¹ @ 10,000 rpm | Overall Length | 78.5 in |
| Maximum Torque | 31.7 lb-ft @ 7,500 rpm | Overall Width | 28.7 in |
| Fuel System | DFI [®] with dual 32mm throttle bodies | Overall Height | 46.5 in |
| Ignition | TCBI with Digital Advance | Ground Clearance | 5.7 in |
| Transmission | 6-speed | Seat Height | 30.9 in |
| Final Drive | Sealed chain | Dry Weight | 348.4 lb** / 350.6 lb** 50-State Model |
| Electronic Rider Aids | Economical Riding Indicator, Anti-lock Brake System (ABS) | Curb Weight | 379.3 lb* / 381.5 lb* 50-State Model |
| PERFORMANCE | | Fuel Capacity | 3.7 gal |
| Front Suspension / Wheel Travel | 41mm hydraulic telescopic fork/4.7 in | Wheelbase | 54.1 in |
| Rear Suspension / Wheel Travel | Horizontal back-link with adjustable spring preload/5.1 in | Special Features | ERGO-FIT [®] , Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP, Kawasaki's Intelligent Proximity Activation Start System (KIPASS), USB-C outlet |
| Front Tire | 110/70-17 | Color Choices | Passion Red/Metallic Flat Spark Black/Metallic Matte Dark Gray |
| Rear Tire | 150/60-17 | Warranty | 12 Month Limited Warranty |

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.