
NINJA H2® ABS









120/70 ZR17 (58W)

200/55 ZR17 (78W)

POWER

Engine Liquid-cooled, 4-stroke, In-Line Four, DOHC, 16-

valve

8 5.1

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression

Maximum Torque

Ratio

DFI® with 50mm throttle bodies (4) with dual **Fuel System**

104.9 lb-ft @ 11,000 rpm

injection; Kawasaki Supercharger

Ignition Digital

Transmission 6-speed, return, dog-ring

Final Drive Sealed chain

Electronic Rider

Aids

Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper

DETAILS

Front Tire

Rear Tire

Front Brakes

Rear Brakes

Trellis, high-tensile steel, with swingarm mounting **Frame Type**

Dual radial-mount, opposed 4-piston Brembo

Opposed 2-piston calipers, single 250mm disc,

Stylema® calipers, dual semi-floating 330mm discs, Kawasaki Intelligent anti-lock Brake System (KIBS)

Kawasaki Intelligent anti-lock Brake System (KIBS)

plate

24.5° / 4.1 in Rake/Trail

Overall Length 82.1 in

Overall Width 30.3 in

Overall Height 44.3 in

Ground Clearance 5.1 in

Seat Height

Curb Weight

Fuel Capacity

Warranty

Wheelbase 57.3 in

Special Features Smartphone Connectivity via RIDEOLOGY THE APP,

all-LED lighting, Highly Durable Paint, TFT

Instrumentation

Color Choices Mirror Coated Spark Black

32.5 in

524.8 lb*

4.5 gal

12 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in

Rear Suspension / Wheel Travel

Uni-Trak®, Öhlins TTX36 gas charged shock with piggyback reservoir, 24-way compression and rebound damping adjustability, 15-way spring preload adjustability, and top-out spring/5.3 in

Scan with camera to view videos. key features and more.

