









160/60 ZR17

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled

Displacement 649cc

Bore x Stroke 83.0 x 60.0mm

Compression

Ratio

10.8:1

Maximum Torque 48.5 lb-ft @ 6,500 rpm

**Fuel System** 

DFI® with Keihin 36mm throttle bodies

Ignition

TCBI with Electronic Advance

**Transmission** 

6-speed, return shift

Final Drive

Sealed chain

**Electronic Rider** 

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock

Brake System (ABS)

	calipers, (and ABS)
Rear Brakes	Single 220mm petal-style disc, (and ABS)
DETAILS	
Frame Type	Trellis, high tensile steel
Rake/Trail	24.0°/3.9 in

Dual 300mm petal-style discs with two-piston

Seat Height	31.1 in

**Rear Tire** 

**Front Brakes** 

**Overall Length** 

**Overall Width** 

**Overall Height** 

Ground

Clearance

**Curb Weight** 414.5 lb\* (ABS) / 412.3 lb\* (non-ABS) 50-State

Model

80.9 in

30.1 in

41.9 in

5.1 in

Fuel Capacity 4.0 gal

Wheelbase 55.5 in

**Special Features** Smartphone Connectivity via RIDEOLOGY THE

APP, TFT Instrumentation

Color Choices Candy Persimmon Red/Ebony, Metallic Matte

Dark Gray/Metallic Spark Black

Warranty 12 Month Limited Warranty

## **PERFORMANCE**

Front Suspension / Wheel Travel Telescopic fork/4.9 in

Rear Suspension / Wheel Travel

Horizontal back-link with adjustable preload,

swingarm/5.1 in

Front Tire 120/70 ZR17

Scan with camera to view videos, key features and more.

