Z900RS CAFE ABS







D	N	M	M	Г	D
Г	U	ľ	٧	E	π

Engine 4-stroke, 4-cylinder, DOHC, 16-valve, liquid-

cooled

10.8:1

Displacement 948cc

Bore x Stroke 73.4 x 56.0mm

Compression

Ratio

Maximum

Horsepower

110.0 hp¹ @ 8,500 rpm

Maximum Torque 72.3 lb-ft @ 6,500 rpm

Fuel System DFI® with Keihin 36mm throttle bodies

Ignition TCBI with Electronic Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider
Aids
Economical Riding Indicator, Kawasaki TRaction
Control (KTRC - 3 Modes), Anti-lock Brake System

(ABS)

PERFORMANCE

Front Suspension / Wheel Travel

41mm inverted telescopic fork with (13-way) adjustable compression and rebound (11-way) damping, spring preload (15-turn)/4.7

Rear Suspension / Wheel Travel

Horizontal back-link swingarm with stepless adjustable rebound damping and spring preload/5.5 in

Front Tire 120/70-17

Rear Tire 180/55-17

Front Brakes Dual 300mm discs with four-piston calipers and

ABS

Rear Brakes Single 250mm disc with single-piston caliper and

ABS

DETAILS

Frame Type Trellis, high tensile steel

Rake/Trail 25.0°/3.9 in

Overall Length 82.7 in

Overall Width 33.3 in

Overall Height 46.9 in

Ground Clearance 5.1 in

Seat Height 32.3 in

Curb Weight 476.2 lb* 50-State Model

Fuel Capacity 4.5 gal

Wheelbase 57.9 in

Color Choices Ebony

Warranty 12 Month Limited Warranty



