MULE™ 4010 4x4









Drum

1,200 lb

POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking N

Alternator Output

CAPABILITY

Front Suspension /

(max)

...

23 amp

Ground Clearance	6.9 in
Fuel Capacity	6.3 gal
Turning Radius	11.2 ft
Cargo Bed Dimensions (LxWxH)	46.3 x 51.6 x 11.4 in
Cargo Bed Load Capacity	800 lb
Payload Capacity	1,327 lb
Seating Capacity	2

(2) Halogen headlights, (2) tail/brake lights

DETAILS

Towing Capacity

Lighting

Rear Brakes

Overall Length 116.7 in

MacPherson Strut/3.9 in Overall Width 62.0 in

Wheel Travel Overall Height 75.8 in

Rear Suspension / DeDion Axle/2.8 in Wheel Travel Curb Weight 1,433.3 lb*

Front Tires 23 x 11-10 Wheelbase 73.6 in

Rear Tires 23 x 11-10 Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type Independent, mechanical drum

Front Brakes Drum

Warranty Kawasaki STRONG 3-Year Limited Warranty



