## **MULE**<sup>™</sup> 4010 4x4 FE







## **POWER**

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking N

Alternator Output 23 amp

(max)

6.9 in

800 lb

Fuel Capacity 6.3 gal

Turning Radius 11.2 ft

Cargo Bed

**Ground Clearance** 

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity 1,312 lb

Seating Capacity

Towing Capacity 1,200 lb

**Lighting** (2) Halogen headlights, (2) tail/brake lights

46.3 x 51.6 x 11.4 in

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / DeDi Wheel Travel

DeDion Axle/2.8 in

 Front Tires
 23 x 11-10

 Rear Tires
 23 x 11-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type Independent, mechanical drum

Front Brakes Drum
Rear Brakes Drum

## **DETAILS**

**Overall Width** 

Overall Length 116.7 in

Overall Height 78.1 in

Curb Weight 1,448.7 lb\*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Additional Features Roof, Horn, Universal Key, High Visibility Orange Seatbelts

Seathetts

62.0 in

Color Choices Bright White

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



