## MULE™ 4010 TRANS4x4®









Drum

## **POWER**

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:

ilipression katio 10.5.1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking N

**Alternator Output** 

(max)

23 amp

<b>Ground Clearance</b>	7.1 in
Fuel Capacity	6.3 gal
Turning Radius	12.8 ft
Cargo Bed Dimensions (LxWxH)	50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4-person)
Cargo Bed Load Capacity	800 lb (2-person) / 401 lb (4-person)
Payload Capacity	1,330 lb
Seating Capacity	2-4
<b>Towing Capacity</b>	1,200 lb

## **CAPABILITY**

Front Suspension /	MacPherson Strut/3.9 in
Wheel Travel	

Rear Suspension /

DeDion Axle/2.8 in

Wheel Travel

23 x 11-10

Rear Tires

23 x 11-10

Steering

**Front Tires** 

Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type

Independent, mechanical drum

Front Brakes Drum

Overall Length

Lighting

Warranty

**DETAILS** 

**Rear Brakes** 

erall Length 128.5 in

Overall Width 58.5 in

Overall Height 75.8 in

Curb Weight 1,587.6 lb\*

Wheelbase 85.2 in

**Instruments** Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

(2) Halogen headlights, (2) tail/brake lights

Color Choices Timberline Green, Dark Royal Red

Kawasaki STRONG 3-Year Limited Warranty



