MULE™ 4010 TRANS4x4® FE







7.7 in

6.3 gal

12.8 ft

1,330 lb

1,200 lb

POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission

Final Drive

with differential lock

Alternator Output 23 amp

(max)

34.7 lb-ft @ 2,500 rpm

Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential

Engine Braking

DETAILS

Lighting

Ground Clearance

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

Dimensions (LxWxH)

Cargo Bed

Capacity

Overall Length 128.5 in

Overall Width 58.5 in

Overall Height 78.1 in

Curb Weight 1,614.1 lb*

Wheelbase 85.2 in

Instruments Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4-

800 lb (2-person) / 401 lb (4-person)

(2) Halogen headlights, (2) tail/brake lights

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White

Warranty Kawasaki STRONG 3-Year Limited Warranty

CAPABILITY

Front Suspension / **Wheel Travel**

MacPherson Strut/3.9 in

DeDion Axle/2.8 in

Rear Suspension / **Wheel Travel**

Front Tires 23 x 11-10 **Rear Tires**

23 x 11-10

Steering

Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type

Independent, mechanical drum

Front Brakes

Drum

Rear Brakes Drum





