2025 **MULE PRO-DXT[™] FE EPS**





BRIGHT WHITE



POWER

Engine	4-stroke, 3-cylinder, OHV, liquid-cooled, diesel	
Displacement	993cc	
Maximum Torque	38.3 lb-ft @ 2,400 rpm	
Bore x Stroke	74.0 x 77.0mm	
Compression Ratio	23.5:1	
Fuel System	Bosch in-line injection pump	
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	
Engine Braking	Yes	
Alternator Output	55 amp	

Fuel Capacity7.9 galTurning Radius16.0 ftCargo Bed Dimensions (LxWxh) $2.7 \times 53.7 \times 11.0$ in (3-person) / 22.0 $\times 53.7 \times 11.0$ in (6- person)Cargo Bed Load Capacity999 lb (3-person) / 350 lb (6-person)Payload Capacity1,574 lbSeating Capacity3-person (1-row), 6-person (2-row)Towing Capacity2,000 lbLighting(2) Halogen headlights	Ground Clearance	10.2 in	
Cargo Bed Dimensions (LxWxH)42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6- person)Cargo Bed Load Capacity999 lb (3-person) / 350 lb (6-person)Payload Capacity1,574 lbSeating Capacity3-person (1-row), 6-person (2-row)Towing Capacity2,000 lb	Fuel Capacity	7.9 gal	
Dimensions (LxWxH)person)Cargo Bed Load Capacity999 lb (3-person) / 350 lb (6-person)Payload Capacity1,574 lbSeating Capacity3-person (1-row), 6-person (2-row)Towing Capacity2,000 lb	Turning Radius	16.0 ft	
CapacityPayload Capacity1,574 lbSeating Capacity3-person (1-row), 6-person (2-row)Towing Capacity2,000 lb	0		
Seating Capacity3-person (1-row), 6-person (2-row)Towing Capacity2,000 lb	0	999 lb (3-person) / 350 lb (6-person)	
Towing Capacity 2,000 lb	Payload Capacity	1,574 lb	
	Seating Capacity	3-person (1-row), 6-person (2-row)	
Lighting (2) Halogen headlights	Towing Capacity	2,000 lb	
	Lighting	(2) Halogen headlights	

DETAILS

	Overall Length	133.3 in
	Overall Width	64.0 in
	Overall Height	79.5 in
	Curb Weight	1,971.3 lb*
	Wheelbase	92.3 in
ring	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
	Additional Features	Roof, Horn, Universal Key, High Visibility Orange Seatbelts
	Color Choices	Bright White
	Warranty	Kawasaki STRONG 3-Year Limited Warranty

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULETM PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE[™] side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.

CAPABILITY

(max)

Wheel Travel	
Rear Suspension / Wheel Travel	Double wishbone/8.5 in (L)/8.7 in (R)
Front Tires	26 x 9-12
Rear Tires	26 x 11-12
Steering	Electric Power Steering (EPS), Tilt steering
Park Brake Type	Independent, mechanical disc
Front Brakes	Dual disc, 2-piston caliper
Rear Brakes	Dual disc, 1-piston caliper

Double wishbone/8.7 in

Scan with camera to view videos, key features and more.

