## **MULE PRO-FXT™ 1000 LE RANCH EDITION**







P	N	V	V	F	R

4-stroke, 2-cylinder, DOHC, liquid-cooled, gas **Engine** 

Displacement 999cc

**Maximum Torque** 61.5 lb-ft @ 4,500 rpm

**Bore x Stroke** 92.0 x 75.1mm

**Compression Ratio** 

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential with **Final Drive** 

differential lock

**Engine Braking** 

**Alternator Output** 90 amp

(max)

12.6 in (max), 11.6 in (std) **Ground Clearance** 

**Fuel Capacity** 7.9 gal

**Turning Radius** 16.0 ft

Dimensions (LxWxH)

**Cargo Bed Load** Capacity

**Payload Capacity** 1,616.3/1,263.5 lb CA Model

**Seating Capacity** 3-person (1 row), 6 person (2 row)

**Towing Capacity** 

Lighting

(2) Halogen headlights, (2) LED headlights

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)

999 lb (3-person)/350 lb (6-person)/348 lb CA Model

## **CAPABILITY**

Front Suspension / Wheel Travel

Double wishbone/11.0 in

Rear Suspension / Wheel Travel

Double wishbone/10.1 in

**Front Tires** 26 x 9-12, radial **Rear Tires** 26 x 11-12, radial

Wheel Type Allov

Steering Rack-and-pinion w/ Electric Power Steering (EPS), Tilt

**Park Brake Type** Independent, mechanical disc **Front Brakes** Dual disc, 2-piston caliper

**Rear Brakes** Dual disc, 1-piston caliper **DETAILS** 

**Overall Length** 135.8 in

**Overall Width** 64.0 in

**Overall Height** 80.9 in

**Estimated Dry Weight** 1,891.9/1,894.1 lb\*\* CA Model

1,966.9/1,969.1 lb\* CA Model **Curb Weight** 

Wheelbase 92.3 in

Multi-function display includes digital speedometer, fuel Instruments

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

**Additional Features** Roof, Additional Front Cup Holders, WARN® VRX 45 Winch,

Premium Seats, Self-Leveling Rear Suspension

**Color Choices** Metallic Deep Red

Kawasaki STRONG 3-Year Limited Warranty Warrantv

Scan with camera to view videos, key features and more.



'Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.