MULE PRO-FXT™ 1000 LE RANCH EDITION









POWFR

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft @ 4,500 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential with

differential lock

Engine Braking Ye

Alternator Output 90 amp

(max)

Ground Clearance 12.6 in (max), 11.6 in (std)

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Dimensions (LxWxH)

Cargo Bed Load

Payload Capacity

Capacity

1,616.3/1,263.5 lb CA Model

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2,000

Lighting (2) Haloge

(2) Halogen headlights, (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/11.0 in

Wheel Travel

Rear Suspension / Wheel Travel

vneet Travet

Double wishbone/10.1 in

Front Tires

26 x 9-12, radial

Rear Tires

26 x 11-12, radial

Wheel Type

Alloy

Steering

Rack-and-pinion w/ Electric Power Steering (EPS), Tilt

steering

Park Brake Type

Independent, mechanical disc

Dual disc, 2-piston caliper

Front Brakes

buut uise, 2 pistoii euripei

Rear Brakes Dual disc, 1-piston caliper

DETAILS

Overall Length 135.8 in

Overall Width

64.0 in

Overall Height

80.9 in

entonic technique

00.9 111

Estimated Dry Weight

1,891.9/1,894.1 lb** CA Model

Curb Weight

1,966.9/1,969.1 lb* CA Model

Wheelbase

92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)

999 lb (3-person)/350 lb (6-person)/348 lb CA Model

indicators, seatbelt reminder lamps

Additional Features

Roof, Additional Front Cup Holders, WARN® VRX 45 Winch,

Premium Seats, Self-Leveling Rear Suspension

Color Choices

Metallic Deep Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.