


UPDATED 2025

MULE PRO-FXT™ 820 EPS



| POWER | | Rear Brakes | |
|---------------------------------|---|------------------------------|---|
| Engine | 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas | Ground Clearance | Dual disc, 1-piston caliper |
| Displacement | 812cc | Fuel Capacity | 10.2 in |
| Maximum Torque | 48.0 lb-ft @ 3,500 rpm | Turning Radius | 7.9 gal |
| Bore x Stroke | 72.0 x 66.5mm | Cargo Bed Dimensions (LxWxH) | 16.0 ft |
| Compression Ratio | 9.5:1 | Cargo Bed Load Capacity | 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person) |
| Fuel System | DFI® with 34mm throttle body | Payload Capacity | 999 lb (3-person)/350 lb (6-person)/348 lb CA Model |
| Transmission | Continuously Variable Transmission (CVT) with (H,L,N,R) | Seating Capacity | 1,616.3/1,263.5 lb CA Model |
| Final Drive | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock | Towing Capacity | 3-person (1 row), 6 person (2 row) |
| Engine Braking | Yes | Lighting | 2,000 lb |
| Alternator Output (max) | 75 amp | | (2) Halogen headlights |
| CAPABILITY | | DETAILS | |
| Front Suspension / Wheel Travel | Double wishbone/8.7 in | Overall Length | 133.3 in |
| Rear Suspension / Wheel Travel | Double wishbone/8.5 in (L)/8.7 in (R) | Overall Width | 64.0 in |
| Front Tires | 26 x 9-12, radial | Overall Height | 77.6 in |
| Rear Tires | 26 x 11-12, radial | Dry Weight | 1,832.4/1,834.6 lb** CA Model |
| Wheel Type | Steel | Curb Weight | 1,911.7/1,913.9 lb* CA Model |
| Steering | Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering | Wheelbase | 92.3 in |
| Park Brake Type | Independent, mechanical disc | Instruments | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps |
| Front Brakes | Dual disc, 2-piston caliper | Color Choices | Timberline Green |
| | | Warranty | Kawasaki STRONG 3-Year Limited Warranty |



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.