## 2025

## **MULE SX™**









## **POWER**

**Engine** 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

**Maximum Torque** 20.6 lb-ft @ 2,200 rpm

82.0 x 76.0mm **Bore x Stroke** 

**Compression Ratio** 8.3:1

**Fuel System** Nikki 6C1026 carburetor

**Transmission** Continuously Variable Transmission (CVT) with (H,L,N,R)

**Final Drive** 2WD, shaft. Dual mode rear differential with differential

lock

**Engine Braking** No

**Alternator Output** 17 amp

(max)

**Front Brakes** Drum **Rear Brakes** Drum **Ground Clearance** 6.1 in **Fuel Capacity** 4.2 gal **Turning Radius** 10.8 ft

Cargo Bed **Dimensions (LxWxH)** 

399 lb

35.6 x 40.9 x 9.6 in

**Cargo Bed Load** Capacity

**DETAILS** 

**Overall Length** 

**Overall Width** 

**Overall Height** 

**Curb Weight** 

**Payload Capacity** 926 lb

**Seating Capacity** 2

**Towing Capacity** 1,100 lb\*\*

Lighting (2) Halogen headlights, tail/brake lights

## **CAPABILITY**

Front Suspension / **Wheel Travel** 

MacPherson Strut/3.1 in

**Rear Suspension / Wheel Travel** 

Unit Swingarm/3.1 in

**Front Tires** 22 x 9-10 **Rear Tires** 22 x 11-10

Rack-and-pinion

**Park Brake Type** 

Steering

Independent, mechanical drum

Wheelbase Instruments

**Color Choices** 

Fuel gauge, hour meter, oil temp light, parking brake

light

70.1 in

106.7 in

52.6 in

70.1 in

967.6 lb\*

Grayish Blue, Super Black

Kawasaki STRONG 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.



\*\*Requires Optional Hitch

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.