

2025

NINJA® 1100SX SE ABS

Kawasaki

Let the Good Times Roll®



EMERALD BLAZED GREEN/METALLIC DIABLO BLACK



POWER		Front Tire	120/70-17
Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled	Rear Tire	190/50-17
Displacement	1,099cc	Front Brakes	Dual 300mm discs with radial-mount 4-piston Brembo M4.32 monobloc calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)
Bore x Stroke	77.0 x 59.0mm	Rear Brakes	Single 260mm disc with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)
Compression Ratio	11.8:1	DETAILS	
Maximum Horsepower	134.0 hp ¹ @ 9,000 rpm	Frame Type	Twin-spar aluminum
Maximum Torque	83.2 lb-ft @ 7,600 rpm	Rake/Trail	24.0° / 3.9 in
Fuel System	DFI® with 38mm Electronic Throttle Valves	Overall Length	82.7 in
Ignition	TCBI with Digital Advance	Overall Width	31.7 in
Transmission	6-speed, return shift with wet multi-disc manual Assist & Slipper Clutch	Overall Height	46.9 in / 48.2 in w/ windshield high
Final Drive	Sealed chain	Ground Clearance	5.3 in
Electronic Rider Aids	Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness	Seat Height	32.3 in
PERFORMANCE		Dry Weight	469.7 lb**
Front Suspension / Wheel Travel	41mm inverted telescopic Showa fork with compression and rebound damping, adjustable spring preload/4.7 in	Curb Weight	516.0 lb*
Rear Suspension / Wheel Travel	Horizontal back-link, Öhlins S46 gas-charged rear shock with rebound damping, remotely adjustable spring preload/5.6 in	Fuel Capacity	5.0 gal
		Wheelbase	56.7 in
		Special Features	4.3" All-digital TFT Instrumentation, All-LED lighting, USB Type-C outlet, Grip heaters, Smartphone Connectivity with Voice Command via RIDELOGY THE APP MOTORCYCLE
		Color Choices	Emerald Blazed Green/Metallic Diablo Black

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.