NINJA® ZX™-14R ABS









POWER

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-

cooled

Displacement 1,441cc

Bore x Stroke 84.0 x 65.0mm

Compression Ratio 12.3:1

Maximum Horsepower 197.0 hp¹ @ 10,000 rpm

Maximum Torque 116.5 lb-ft @ 7,500 rpm

DFI® with 44mm Mikuni throttle bodies (4) **Fuel System**

Ignition TCBI with Electronic Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Power Modes, Anti-lock

Brake System (ABS)

PERFORMANCE

Front Suspension / **Wheel Travel**

43mm inverted cartridge fork with adjustable preload, 18-way compression and 15-way rebound damping adjustment/4.6 in

Rear Suspension / Wheel Travel

Bottom-link Uni-Trak® and gas-charged shock with adjustable preload, stepless rebound and compression damping adjustments, adjustable ride

height/4.9 in

Front Tire 120/70-17

Rear Tire 190/50-R17

Front Brakes Dual 310mm semi-floating Brembo discs with dual

radial-mounted Brembo 4-piston M50 monobloc

Rear Brakes Single 250mm disc with twin-piston caliper and ABS

DETAILS

Frame Type Aluminum monocoque

Rake/Trail 23.0°/3.7 in

Overall Length 85.4 in

Overall Width 30.3 in

Overall Height 46.1 in

Ground Clearance 4.9 in

Seat Height 31.5 in

Curb Weight 593.1 lb*

Fuel Capacity 5.8 gal

Wheelbase 58.3 in

Color Choices Metallic Matte Sovereign Red/Metallic Flat Spark

Black/Metallic Matte Graphite Gray

12 Month Limited Warranty Warranty

Scan with camera to view videos, key features and more.

