
## NINJA® ZX™-4R ABS









## **POWER**

4-stroke, in-line 4-cylinder, DOHC, 16-valve, **Engine** 

liquid-cooled

Displacement 399cc

**Bore x Stroke** 57.0 x 39.1mm

Compression **Ratio** 

Maximum

Horsepower

56.0 hp<sup>1</sup> @ 11,500 rpm

**Maximum Torque** 26.5 lb-ft @ 11,000 rpm

12.3:1

**Fuel System** DFI® with 34mm throttle valves (4)

Ignition TCBI with Digital Advance

**Transmission** 6-speed, return shift

**Final Drive** Chain

**Electronic Rider** 

**Aids** 

Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Power Modes, Anti-lock

Brake System (ABS)

## **PERFORMANCE**

**Front Suspension** / Wheel Travel

37mm inverted Showa fork with SFF-BP

internals/4.7 in

**Rear Suspension** Horizontal back-link, Showa shock w/ adjustable / Wheel Travel

spring preload/4.4 in

**Front Tire** 110/70-17

**Rear Tire** 160/60-17

**Front Brakes** Dual 290mm semi-floating discs with radial-

mount 4-piston monobloc caliper and ABS

Single 220mm disc with single-piston caliper and **Rear Brakes** 

ABS

## **DETAILS**

Trellis, high-tensile steel **Frame Type** 

Rake/Trail 23.5°/3.8 in

**Overall Length** 78.3 in

**Overall Width** 30.1 in

**Overall Height** 43.7 in

**Ground Clearance** 5.3 in

**Seat Height** 31.5 in

**Curb Weight** 414.5 lb\*

**Fuel Capacity** 4.0 gal

Wheelbase 54.3 in

**Special Features** 4.3" Full-color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

**Color Choices** Metallic Spark Black

Warranty 12 Month Limited Warranty



