## **BRUTE FORCE® 750**









## **POWER**

**Engine** 4-stroke, V-twin, SOHC, liquid-cooled

749cc Displacement

85.0 x 66.0mm **Bore x Stroke** 

**Compression Ratio** 

Maximum Horsepower 50.0 hp1 @ 6,750 rpm **Maximum Torque** 42.8 lb-ft @ 4,750 rpm

DFI® with two 34mm throttle bodies **Fuel System** 

Ignition Digital DC-CDI

Automatic Continuously Variable Transmission (CVT) with **Transmission** 

(H,L,N,R)

**Final Drive** Selectable 2WD/4WD with variable control front differential lock,

## **DETAILS**

Tread Width

**Fuel Capacity** 

**Turning Radius** 

**Towing Capacity** 

**Total Rack Capacity** 

Rack Capacity, Front/

Steering

Rear Lighting

Double-cradle, high-tensile tubular steel **Frame Type** 37.0/35.6 in

5.0 gal

10.5 ft

1.250 lb

264.5 lb

88.0/176.0 lb

All-LED lighting

Rack-and-pinion

**Overall Length** 86.0 in Overall Width 46.1 in **Overall Height** 47.6 in **Seat Height** 35.2 in **Estimated Dry Weight** 661.5 lb\*\* **Curb Weight** 707.8 lb\*

Wheelbase 50.6 in

Instruments

Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h),

battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant

temperature, CVT, oil, and battery voltage)

Full-color TFT Instrumentation w/ Smartphone Connectivity via **Special Features** 

RIDEOLOGY THE APP POWERSPORTS, KQR™ system

**Color Choices** Firecracker Red

Warranty 12 Month Limited Warranty

## CAPABILITY

Front Suspension / **Wheel Travel** 

Double wishbone, adjustable spring preload/6.9 in

Rear Suspension / Wheel Travel

Double wishbone, adjustable spring preload/7.4 in

**Front Tires** 

AT 25 x 8-12 AT 25 x 10-12

**Rear Tires** 

Dual hydraulic 176mm discs with 2-piston calipers

**Front Brakes** Rear Brakes

Sealed, oil-bathed, multi-disc with independent park brake

**Ground Clearance** 

9.0 in/9.7 in (max preload)

**Starting System** 

**Flectric** 

Scan with camera to view videos, key features and more



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. © 2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.