²⁰²⁶ **KLX®140R**







POWER		Front Brakes	Single 220mm petal disc with a dual-piston caliper
Engine	4-stroke, single-cylinder, SOHC, air-cooled	Rear Brakes	Single 186mm petal disc with single-piston caliper
Displacement	144cc		
Bore x Stroke	58.0 x 54.4mm	DETAILS	
Compression Ratio	9.5:1	Frame Type	High-tensile steel, box-section perimeter
Fuel System	Keihin PB20 carburetor	Rake/Trail	27.0°/3.3 in
Ignition	Digital DC-CDI	Overall Length	71.7 in
Transmission	5-speed, return shift, with wet multi-disc manual clutch	Overall Width	31.1 in
		Overall Height	41.3 in
Final Drive	Chain	Ground	9.3 in
PERFORMANCE		Clearance Seat Height	30.7 in
		Ū	
Front Suspension /	33mm telescopic fork/7.1 in	Estimated Dry Weight	191.7 lb**
Wheel Travel		Curb Weight	205.0 lb*
Rear Suspension /	Uni-Trak® linkage system and single shock with 5-way preload adjustability/7.1 in	Fuel Capacity	1.5 gal
Wheel Travel		Wheelbase	49.6 in
Front Tire	70/100-17	Color Choices	Lime Green, Bright White
Rear Tire	90/100-14	Warranty	6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.