

2026

KLX[®]150



POWER

Engine	4st, 1-cyl, SOHC, A/C
Displacement	144cc
Bore x Stroke	58.0 x 54.4 mm
Compression Ratio	9.5:1
Fuel System	Carburettor: NCV24
Ignition	DC-CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

PERFORMANCE

Front Suspension / Wheel Travel	Horquilla telescópica/185 mm
Rear Suspension / Wheel Travel	Uni-Trak [®] swingarm/192 mm
Front Tire	2.75-21 45P

Rear Tire	4.10-18 59P
Front Brakes	Single disc
Rear Brakes	Single disc

DETAILS

Frame Type	Perimeter, steel
Rake/Trail	26.9° / 110 mm
Overall Length	2,050 mm
Overall Width	830 mm
Overall Height	1,155 mm
Ground Clearance	300 mm
Seat Height	865 mm
Curb Weight	118 kg*
Fuel Capacity	6.9 L
Wheelbase	1,345 mm
Color Choices	Lime Green

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.