KLX[®]230R S









POWER

4-stroke, single-cylinder, SOHC, air-cooled **Engine**

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

DFI® with 32mm Keihin throttle body **Fuel System**

Ignition TCBI with electronic advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain **Front Brakes**

Single 240mm petal disc with a dual-piston

caliper

Rear Brakes

DETAILS

Single 220mm petal disc with single-piston

caliper

Frame Type High-tensile steel, box-section perimeter

Rake/Trail 24.6°/3.9 in

80.5 in **Overall Length**

Overall Width 33.3 in

Overall Height 46.7 in

Ground 10.6 in Clearance

Seat Height 34.4 in

Estimated Dry

Weight

247.0 lb** / 249.1 lb** 50-State Model

Curb Weight 262.4 lb* / 264.5 lb* 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.3 in

Color Choices Lime Green, Bright White

Warranty 6 Month Limited Warranty

PERFORMANCE

37mm telescopic fork/8.7 in **Front** Suspension / **Wheel Travel** Rear Suspension /

Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in

Front Tire 80/100-21

Rear Tire 100/100-18

Scan with camera to view videos, key features and more.

Wheel Travel

