KLX®230R S









P	N	V	V	F	R
					-

Engine 4-stroke, single-cylinder, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression Ratio 9.4:1

Fuel System DFI® with 32mm Keihin throttle body

Ignition TCBI with electronic advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

Front Brakes

Single 240mm petal disc with a dual-piston

caliper

Rear Brakes

Single 220mm petal disc with single-piston

caliper

PERFORMANCE

Front
Suspension /
Wheel Travel

Rear
Suspension /
Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in

Front Tire

80/100-21

Rear Tire

100/100-18

DETAILS

Frame Type High-tensile steel, box-section perimeter

Rake/Trail 24.6°/3.9 in

Overall Length 80.5 in

Overall Width 33.3 in

Overall Height 46.7 in

Ground 10.6 in Clearance

Seat Height 34.4 in

Estimated Dry 247.0 lb** / 249.1 lb** 50-State Model

Weight

Curb Weight 262.4 lb* / 264.5 lb* 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.3 in

Color Choices Lime Green, Bright White

Warranty 6 Month Limited Warranty



