







Dſ	11	M	С	D
Γl	J١	V	C	π

Engine 4-stroke, single-cylinder, DOHC, liquid-cooled

Displacement 249cc

Bore x Stroke 78.0 x 52.2mm

Compression

Ratio

14.1:1

Fuel System DFI® with 44mm Keihin throttle body and dual

injectors

Ignition Digital DC-CDI

Transmission 5-speed, return shift, with wet multi-disc

manual clutch and hydraulic clutch actuation

Final Drive Chain

Electronic Rider

Aids

Power Modes, Kawasaki TRaction Control

(KTRC), Launch Control Mode

PERFORMANCE

Front
Suspension /
Wheel Travel

49mm Showa inverted telescopic coil-spring fork with 16-way compression and rebound damping /12.0 in

damping / iz.o

Rear Uni-Trak® with dual-range (4 turns high speed/19-way low-speed) compression damping, 22-way rebound damping and

adjustable preload/12.1 in

Front Tire 80/100-21

Rear Tire 110/90-19

Front Brakes Single semi-floating 270mm Braking petal disc

with dual-piston caliper

Rear Brakes Single 240mm Braking petal disc with single-

piston caliper

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 27.0°/4.6 in

Overall Length 86.2 in

Overall Width 32.3 in

Overall Height 49.8 in

Ground 13.4 in

Clearance

Seat Height 37.6 in

Curb Weight 230.9 lb* without fuel / 240.8 lb*

Fuel Capacity 1.64 gal

Wheelbase 58.5 in

Special Features Smartphone Connectivity via RIDEOLOGY THE

APP KX™, ERGO-FIT®

Color Choices Lime Green

Warranty Not Available



