



2026

MULE PRO-DX™ EPS




-  TIMBERLINE GREEN
-  SUPER BLACK



POWER		Rear Brakes	
Engine	4-stroke, 3-cylinder, OHV, liquid-cooled, diesel	Ground Clearance	Dual disc, 1-piston caliper
Displacement	993cc	Fuel Capacity	10.4 in
Maximum Horsepower	24.0 hp ¹ @ 3,600 rpm	Turning Radius	7.9 gal
Maximum Torque	38.3 lb-ft @ 2,400 rpm	Cargo Bed Dimensions (LxWxH)	16.0 ft
Bore x Stroke	74.0 x 77.0mm	Cargo Bed Load Capacity	54.1 x 53.7 x 11.0 in
Compression Ratio	23.5:1	Payload Capacity	999 lb
Fuel System	Bosch in-line injection pump	Seating Capacity	1,574 lb
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Towing Capacity	3-person
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Lighting	2,000 lb
Engine Braking	Yes	DETAILS	
Alternator Output (max)	55 amp		
CAPABILITY		Overall Length	133.3 in
Front Suspension / Wheel Travel	Double wishbone/8.7 in	Overall Width	64.0 in
Rear Suspension / Wheel Travel	Double wishbone/8.5 in (L)/8.7 in (R)	Overall Height	77.4 in
Front Tires	26 x 9-12	Estimated Dry Weight	1,799.3 lb**
Rear Tires	26 x 11-12	Curb Weight	1,885.3 lb*
Steering	Electric Power Steering (EPS), Tilt steering	Wheelbase	92.3 in
Park Brake Type	Independent, mechanical disc	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Front Brakes	Dual disc, 2-piston caliper	Color Choices	Timberline Green, Super Black
		Warranty	Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.