## **MULE PRO-DXT™ EPS**









## **POWER**

4-stroke, 3-cylinder, OHV, liquid-cooled, diesel **Engine** 

993cc Displacement

**Maximum Horsepower** 24.0 hp1 @ 3,600 rpm **Maximum Torque** 38.3 lb-ft @ 2,400 rpm

74.0 x 77.0mm Bore x Stroke

**Compression Ratio** 23.5:1

Bosch in-line injection pump **Fuel System** 

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential with **Final Drive** 

differential lock

**Engine Braking** Yes

**Alternator Output** 55 amp

(max)

**Ground Clearance** 10.2 in **Fuel Capacity** 7.9 gal

**Turning Radius** 16.0 ft

**Cargo Bed Dimensions** 

(LxWxH)

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)

Cargo Bed Load

Capacity

999 lb (3-person) / 350 lb (6-person)

**Payload Capacity** 1.574 lb

**Seating Capacity** 3-person (1-row), 6-person (2-row)

**Towing Capacity** 2.000 lb

Lighting (2) Halogen headlights

## CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/8.7 in

Rear Suspension / **Wheel Travel** 

Double wishbone/8.5 in (L)/8.7 in (R)

**Front Tires** 26 x 9-12

**Rear Tires** 26 x 11-12

Electric Power Steering (EPS), Tilt steering **Steering** 

**Park Brake Type** Independent, mechanical disc **Front Brakes** Dual disc, 2-piston caliper

**Rear Brakes** Dual disc, 1-piston caliper

## **DETAILS**

**Overall Length** 133.3 in

**Overall Width** 64.0 in

**Overall Height** 77.6 in

**Estimated Dry Weight** 1.898.5 lb\*\*

**Curb Weight** 1.984.5 lb\*

Wheelbase 92.3 in

Multi-function display includes digital speedometer, fuel Instruments

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

**Additional Features** Roof, Horn, Universal Key, High Visibility Orange Seatbelts

**Color Choices** Super Black

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.