MULE PRO-FX™ 1000 HD EDITION









POWER

4-stroke, 2-cylinder, DOHC, liquid-cooled, gas Engine

Displacement

Maximum Horsepower 70.0 hp1 @ 6,500 rpm 61.5 lb-ft @ 4,500 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

Maximum Torque

10.1:1 DFI® with 38mm throttle body **Fuel System**

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential with

90 amp

Engine Braking Yes

Alternator Output

(max)

Ground Clearance 11.9 in (max), 11.8 in (std)

Fuel Capacity 7.9 gal **Turning Radius** 16.0 ft

Cargo Bed Dimensions 54.1 x 53.3 x 11.0 in (LxWxH)

Cargo Bed Load

999/600 lb CA Model

Capacity **Payload Capacity**

DETAILS

Overall Length

Overall Width

Overall Height

Curb Weight

Wheelbase

Instruments

Estimated Dry Weight

1,616.3/1,263.5 lb CA Model

1,830.2/1,832.4 lb** CA Model

1.913.9/1.916.1 lb* CA Model

Seating Capacity

2,000 lb **Towing Capacity**

Lighting (2) Halogen headlights, (2) LED headlights

136.6 in

64 0 in

81.1 in

92.3 in

CAPABILITY

Front Suspension /

Wheel Travel

Double wishbone / 11.0 in

Rear Suspension / Wheel Travel

Double wishbone / 10.1 in

Front Tires

26 x 9-12, radial

Rear Tires

26 x 11-12, radial

Steering

Rack-and-pinion

Park Brake Type

Independent, mechanical disc

Front Brakes

Dual disc, 2-piston caliper

Rear Brakes

Dual disc, 1-piston caliper

Wheel Type

Additional Features

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure

warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt

reminder lamps

Roof, Rear Bumper, Additional Under Seat Storage Bin, Rearview Mirror, Hydraulic Cargo Bed Lift, Self-Leveling Rear Suspension,

Anti-cinch Seatbelts

Color Choices Firecracker Red

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.