

2026

MULE PRO-FX™ 820 EPS

Kawasaki

Let the Good Times Roll®



- TIMBERLINE GREEN
- DARK ROYAL RED



POWER		Rear Brakes	
Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas	Ground Clearance	Dual disc, 1-piston caliper
Displacement	812cc	Fuel Capacity	10.4 in
Maximum Torque	48.0 lb-ft @ 3,500 rpm	Turning Radius	7.9 gal
Bore x Stroke	72.0 x 66.5mm	Cargo Bed Dimensions (LxWxH)	16.0 ft
Compression Ratio	9.5:1	Cargo Bed Load Capacity	54.1 x 53.3 x 11.0 in
Fuel System	DFI® with 34mm throttle body (3)	Payload Capacity	999/600 lb CA Model
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Seating Capacity	1,616.3/1,263.5 lb CA Model
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Towing Capacity	3
Engine Braking	Yes	Lighting	2,000 lb
Alternator Output (max)	75 amp		(2) Halogen headlights
CAPABILITY		DETAILS	
Front Suspension / Wheel Travel	Double wishbone/8.7 in	Overall Length	133.3 in
Rear Suspension / Wheel Travel	Double wishbone/8.5 in (L)/8.7 in (R)	Overall Width	64.0 in
Front Tires	26 x 9-12, radial	Overall Height	77.4 in
Rear Tires	26 x 11-12, radial	Estimated Dry Weight	1,770.6/1,772.8 lb** CA Model
Wheel Type	Alloy	Curb Weight	1,852.2/1,854.4 lb* CA Model
Steering	Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering	Wheelbase	92.3 in
Park Brake Type	Independent, mechanical disc	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps
Front Brakes	Dual disc, 2-piston caliper	Color Choices	Timberline Green, Dark Royal Red
		Warranty	Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.