## **MULE PRO-FXR™ 1000 LE**









## **POWER**

4-stroke, 2-cylinder, DOHC, liquid-cooled, gas **Engine** 

**Displacement** 999cc

**Maximum Horsepower** 70.0 hp1 @ 6,500 rpm **Maximum Torque** 61.5 lb-ft @ 4,500 rpm

**Bore x Stroke** 92.0 x 75.1mm

**Compression Ratio** 10.1:1

DFI® with 38mm throttle body **Fuel System** 

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential with

differential lock

**Engine Braking** Yes

Alternator Output 90 amp

(max)

**Ground Clearance** 13.2 in (max), 12.2 in (std)

**Fuel Capacity** 7.9 gal **Turning Radius** 14.0 ft

**Cargo Bed Dimensions** 37.6 x 53.3 x 11.0 in

(LxWxH)

Cargo Bed Load Capacity

**DETAILS** 

**Overall Length** 

**Overall Width** 

**Overall Height** 

**Curb Weight** 

Wheelbase

Instruments

**Estimated Dry Weight** 

999/600 lb CA Model

1,616.3/1,263.5 lb CA Model **Payload Capacity** 

**Seating Capacity** 

**Towing Capacity** 2,000 lb

Lighting (2) Halogen headlights, (2) LED headlights

122.0 in

64.0 in

78.5 in

79.7 in

## **CAPABILITY**

Double wishbone/11.0 in Front Suspension / Wheel Travel

Rear Suspension / Wheel Travel

Double wishbone/10.1 in

**Front Tires** 27 x 9-12, radial **Rear Tires** 27 x 11-12, radial

Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering Steering

Independent, mechanical disc Park Brake Type

**Front Brakes** Dual disc, 2-piston caliper

**Rear Brakes** Dual disc, 1-piston caliper

indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS

warning indicators, neutral, reverse and parking indicators,

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD

seatbelt reminder lamps

1,684.6/1,686.8 lb\*\* CA Model

1,768.4/1,770.6 lb\* CA Model

Wheel Type Alloy

**Additional Features** Roof, Rear Bumper, Contoured Two-Tone Bench Seat,

Additional Cup Holders

**Color Choices** Candy Persimmon Red

Scan with camera to view videos, key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.