MULE PRO-FXT™ 1000 PLATINUM RANCH EDITION









POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Horsepower 70.0 hp1 @ 6,500 rpm **Maximum Torque** 61.5 lb-ft @ 4,500 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential with

differential lock

Engine Braking Alternator Output 90 amp

(max)

Fuel Capacity

Cargo Bed Dimensions

Cargo Bed Load

Capacity

Lighting

7.9 gal

16.0 ft

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)

999 lb (3-person)/350 lb (6-person)/348 lb CA Model

1,466.3/1,162.0 lb CA Model

3-person (1 row), 6 person (2 row)

Towing Capacity 2.000 lb

(4) LED headlights

CAPABILITY

Front Suspension /

Wheel Travel

Double wishbone/11.0 in

Rear Suspension / Wheel Travel

Double wishbone/10.1 in

Front Tires

26 x 9-12, radial 26 x 11-12, radial

Rear Tires

Steering

Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering

Park Brake Type

Dual disc, 2-piston caliper

Independent, mechanical disc

Front Brakes **Rear Brakes**

Dual disc, 1-piston caliper 12.6 in (max), 11.6 in (std)

Ground Clearance

Turning Radius

(LxWxH)

Payload Capacity

Seating Capacity

DETAILS

Overall Length 140.2 in

Overall Width

64.0 in

Overall Height

80.9 in

Estimated Dry Weight

1,988.9/1,991.1 lb** CA Model

Curb Weight

2,072.7/2,074.9 lb* CA Model

Wheelbase

92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

Wheel Type

Additional Features

Allov

Roof, Additional Front Cup Holders, WARN® VRX 45 Winch, Premium Seats, Premium Shoulder Pads, Self-Leveling Rear Suspension, Quad LED Headlights, Brush Guard, Headlight Guards, Rear Bumper, Anti-cinch Seat Belts, Rearview Mirror,

Additional Under Seat Storage Bin

Color Choices Metallic Deep Red

Scan with camera to view videos, key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.