

2026

MULE PRO-FXT™ 1000 PLATINUM RANCH EDITION



| POWER | | Details | |
|---------------------------------|---|------------------------------|--|
| Engine | 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas | Ground Clearance | 12.6 in (max), 11.6 in (std) |
| Displacement | 999cc | Fuel Capacity | 7.9 gal |
| Maximum Horsepower | 70.0 hp ¹ @ 6,500 rpm | Turning Radius | 16.0 ft |
| Maximum Torque | 61.5 lb-ft @ 4,500 rpm | Cargo Bed Dimensions (LxWxH) | 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person) |
| Bore x Stroke | 92.0 x 75.1mm | Cargo Bed Load Capacity | 999 lb (3-person)/350 lb (6-person)/348 lb CA Model |
| Compression Ratio | 10.1:1 | Payload Capacity | 1,466.3/1,162.0 lb CA Model |
| Fuel System | DFI® with 38mm throttle body | Seating Capacity | 3-person (1 row), 6 person (2 row) |
| Transmission | Continuously Variable Transmission (CVT) with (H,L,N,R) | Towing Capacity | 2,000 lb |
| Final Drive | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock | Lighting | (4) LED headlights |
| Engine Braking | Yes | DETAILS | |
| Alternator Output (max) | 90 amp | Overall Length | 140.2 in |
| CAPABILITY | | Overall Width | 64.0 in |
| Front Suspension / Wheel Travel | Double wishbone/11.0 in | Overall Height | 80.9 in |
| Rear Suspension / Wheel Travel | Double wishbone/10.1 in | Estimated Dry Weight | 1,988.9/1,991.1 lb** CA Model |
| Front Tires | 26 x 9-12, radial | Curb Weight | 2,072.7/2,074.9 lb* CA Model |
| Rear Tires | 26 x 11-12, radial | Wheelbase | 92.3 in |
| Wheel Type | Alloy | Instruments | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps |
| Steering | Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering | Additional Features | Roof, Additional Front Cup Holders, WARN® VRX 45 Winch, Premium Seats, Premium Shoulder Pads, Self-Leveling Rear Suspension, Quad LED Headlights, Brush Guard, Headlight Guards, Rear Bumper, Anti-cinch Seat Belts, Rearview Mirror, Additional Under Seat Storage Bin |
| Park Brake Type | Independent, mechanical disc | Color Choices | Metallic Deep Red |
| Front Brakes | Dual disc, 2-piston caliper | | |
| Rear Brakes | Dual disc, 1-piston caliper | | |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.