

NEW 2026

NINJA® ZX™-10R

Kawasaki
Let the Good Times Roll®



LIME GREEN/BLUE 24

METALLIC MATTE GRAPHENESTEEL GRAY/
METALLIC SPARK BLACK/PEARL STORM GRAY

POWER

| | |
|------------------------------|--|
| Engine | 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled |
| Displacement | 998cc |
| Bore x Stroke | 76.0 x 55.0mm |
| Compression Ratio | 13.0:1 |
| Maximum Horsepower | 190.0 hp ¹ @ 11,500 rpm |
| Maximum Torque | 82.5 lb-ft @ 11,300 rpm |
| Fuel System | DFI® with 47mm throttle bodies |
| Ignition | TCBI with Electronic Advance |
| Transmission | 6-speed, return shift |
| Final Drive | Sealed chain |
| Electronic Rider Aids | Economical Riding Indicator, Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Anti-lock Brake System (ABS) (ABS only), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Engine Brake Control, Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness |

PERFORMANCE

| | |
|--|---|
| Front Suspension / Wheel Travel | 43mm inverted Showa Balance Free Fork (BFF) with external compression chamber, rebound and compression damping, spring preload adjustability/4.7 in |
| Rear Suspension / Wheel Travel | Horizontal back-link with Showa Balance Free Rear Cushion (BFR) lite gas-charged shock with piggyback reservoir, rebound and compression damping, spring preload adjustability/4.2 in |

| | |
|---------------------|---|
| Front Tire | 120/70 ZR17 |
| Rear Tire | 190/55 ZR17 |
| Front Brakes | Dual 330mm semi-floating Brembo discs with radial-mount 4-piston Brembo M50 monobloc calipers (and ABS) |
| Rear Brakes | Single 220mm disc with aluminum single-piston caliper (and ABS) |

DETAILS

| | |
|-----------------------------|--|
| Frame Type | Twin spar, cast aluminum |
| Rake/Trail | 25.0° / 4.1 in |
| Overall Length | 82.1 in |
| Overall Width | 29.5 in |
| Overall Height | 46.5 in |
| Ground Clearance | 5.1 in |
| Seat Height | 32.5 in |
| Estimated Dry Weight | 425.6 lb** (ABS), 421.2 lb** (non-ABS) 49-State Model |
| Curb Weight | 463.1 lb* (ABS), 458.6 lb* (non-ABS) 49-State Model |
| Fuel Capacity | 4.5 gal |
| Wheelbase | 57.1 in |
| Special Features | 5" All-digital TFT color instrumentation, All-LED lighting, Öhlins steering damper, Smartphone Connectivity with available Voice Command and Turn-by-Turn Navigation via RIDEOLOGY THE APP MOTORCYCLE*** |
| Color Choices | Lime Green/Blue 24, Metallic Matte Graphenesteel Gray/Metallic Spark Black/Pearl Storm Gray |
| Warranty | 12 Month Limited Warranty |

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

***RIDEOLOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.