TERYX KRX® 1000







SMOKY GRAY/SUPER BLACK



GRAYISH BLUE/SUPER BLACK



POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

 Maximum Horsepower
 110.0 hp¹ @ 8,500 rpm

 Maximum Torque
 75.2 lb-ft @ 7,000 rpm

 Bore x Stroke
 92.0 x 75.1mm

Compression Ratio 11.5:1

Fuel System DFI® with (2) 50mm throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

Turning Radius 20.3 ft

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in

(LxWxH)

Cargo Bed Load 351 lb

Capacity

Payload Capacity 781 lb

Seating Capacity

Towing Capacity N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / Double wishbone, Showa 2.5 shocks with piggyback reservoir, Wheel Travel fully adjustable preload, and 24-position adjustable

compression damping/18.6 in

Rear Suspension / 4-link trailing-arm rear suspension, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position

adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes 258mm dual hydraulic discs with 2-piston calipers

Rear Brakes 258mm dual hydraulic discs with single-piston calipers

Ground Clearance 14.8 in (max) / 14.2 in (std)

Fuel Capacity 10.6 gal

DETAILS

Frame Ladder type, tubular steel

2

Overall Length 130.1 in
Overall Width 68.1 in
Overall Height 74.8 in

Estimated Dry Weight 1,794.9 lb** / 1,797.1 lb** CA Model

Curb Weight 1,894.1 lb* / 1,896.3 lb* CA Model

Wheelbase 98.8 in

Instruments Multi-function digital meter with bar-style tachometer (2 display

options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and

CVT belt warning lamp

Wheel Type Alloy with bead-lock wheels

Additional Features Steel skid-plates w/ drain holes

Color Choices Smoky Gray/Super Black, Grayish Blue/Super Black

Warranty 6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.