## TERYX KRX® 1000 BLACKOUT EDITION









## **POWER**

Ignition

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement

Maximum Horsepower 110.0 hp1 @ 8,500 rpm **Maximum Torque** 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

**Compression Ratio** 

DFI® with (2) 50mm throttle bodies **Fuel System** 

Starting System Flectric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

**Final Drive** Selectable 2WD/4WD with locking front differential, shaft

TCBI with electronic advance

**Engine Braking** Yes Cargo Bed Load Capacity

**Cargo Bed Dimensions** 

(LxWxH)

351 lb 781 lb

N/A

14.6 x 33.1 x 9.1 in

**Payload Capacity Seating Capacity** 

**Towing Capacity** 

Lighting

(2) LED headlights, (2) LED taillights, LED stoplight, (4) LED light bars

## **DETAILS**

Ladder type, tubular steel

**Overall Length** 133.3 in **Overall Width** 68.1 in **Overall Height** 76.0 in

**Estimated Dry Weight** 1,931.6 lb\*\* / 1,933.8 lb\*\* CA Model **Curb Weight** 2,030.8 lb\* / 2,033.0 lb\* CA Model

Wheelbase

Instruments

Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, barstyle CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp

Wheel Type Alloy with bead-lock wheels

**Additional Features** 

Warranty

LED light bars (38-in mounted to front of roof, 8-in mounted to front bumper, (2) 8-in mounted to rear of roof), Front Bumper, Rear Bumper, Steel skid-plates w/ drain holes, KQR™ Premium Roof, Hifonics® Audio System, WARN® VRX 45 Powersport Winch

**Color Choices** Flat Ebony

6 Month Limited Warranty

## **CAPABILITY**

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in

Rear Suspension / Wheel Travel

Steering

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in

**Front Tires** Maxxis® Carnivore 31 x 10.00R15 8PR **Rear Tires** Maxxis® Carnivore 31 x 10.00R15 8PR

Electric Power Steering (EPS) / rack-and-pinion

Front Brakes 258mm dual hydraulic discs with 2-piston calipers

258mm dual hydraulic discs with single-piston calipers **Rear Brakes** 

**Ground Clearance** 14.0 in (max), 13.4 in (std)

**Fuel Capacity** 10.6 gal **Turning Radius** 20.3 ft

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.