TERYX® KRX4™ 1000





SMOKY GRAY/SUPER BLACK

GRAYISH BLUE/SUPER BLACK





POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 9999

 Maximum Horsepower
 110.0 hp¹ @ 8,500 rpm

 Maximum Torque
 75.2 lb-ft @ 7,000 rpm

 Bore x Stroke
 92.0 x 75.1mm

Compression Ratio 11.5:

Fuel System DFI® with (2) 50mm throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

Turning Radius 23.3 ft

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in

(LxWxH)

Cargo Bed Load Capacity 351 lb

Payload Capacity 1,001 lb
Seating Capacity 4

Towing Capacity N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / Double wishbone, Showa 2.5 shocks with piggyback reservoir, fully Wheel Travel adjustable preload, and 24-position adjustable compression

damping/18.6 in

Rear Suspension / 4-link trailing-arm rear suspension, Showa 2.5 shocks with Wheel Travel piggyback reservoir, fully adjustable preload, and 24-position

adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Electric Power Steering (EPS) / rack-and-pinion

Front Brakes 258mm dual hydraulic discs with 2-piston calipers

Rear Brakes 258mm dual hydraulic discs with single-piston calipers

Ground Clearance 14.8 in (max), 14.2 in (std)

Fuel Capacity 10.6 gal

Towning Capac

DETAILS

Frame

Ladder type, tubular steel

Overall Length 157.3 in
Overall Width 68.1 in
Overall Height 76.2 in

Estimated Dry Weight 1,997.7 lb** / 1,999.9 lb** CA Model

Curb Weight 2,099.2 lb* / 2,101.4 lb* CA Model

Wheelbase 125.8

Instruments Multi-function digital meter with bar-style tachometer (2 display

options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS

warning lamp, and CVT belt warning lamp

Wheel Type Alloy

Additional Features Steel skid-plates w/ drain holes

Color Choices Smoky Gray/Super Black, Grayish Blue/Super Black

Warranty 6 Month Limited Warranty

Scan with camera to view videos, key features and more.

Steering



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.