

2026

TERYX® KRX4™ 1000 eS

Kawasaki


Let the Good Times Roll®

 SKY BLUE/SUPER BLACK



POWER		Turning Radius	23.3 ft
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Displacement	999cc	Cargo Bed Load Capacity	351 lb
Maximum Horsepower	110.0 hp ¹ @ 8,500 rpm	Payload Capacity	1,001 lb
Maximum Torque	75.2 lb-ft @ 7,000 rpm	Seating Capacity	4
Bore x Stroke	92.0 x 75.1mm	Towing Capacity	N/A
Compression Ratio	11.5:1	Lighting	(2) LED headlights, (2) LED taillights, LED sto­plight
Fuel System	DFI® with (2) 50mm throttle bodies	DETAILS	
Ignition	TCBI with electronic advance	Frame	Ladder type, tubular steel
Starting System	Electric	Overall Length	157.3 in
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	Overall Width	68.1 in
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Overall Height	76.2 in
Engine Braking	Yes	Estimated Dry Weight	2,006.6 lb** / 2,008.8 lb** CA Model
CAPABILITY		Curb Weight	2,108.0 lb* / 2,110.2 lb* CA Model
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in	Wheelbase	125.8 in
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in	Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
Front Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Wheel Type	Alloy
Rear Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Additional Features	Steel skid-plates w/ drain holes, TFT Full-Color Instrumentation with Smartphone Connectivity
Steering	Electric Power Steering (EPS) / rack-and-pinion	Color Choices	Sky Blue/Super Black
Front Brakes	258mm dual hydraulic discs with 2-piston calipers	Warranty	6 Month Limited Warranty
Rear Brakes	258mm dual hydraulic discs with single-piston calipers		
Ground Clearance	15.2 in (max), 14.2 in (std)		
Fuel Capacity	10.6 gal		

Scan with camera to view videos, key features and more.



^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.