

2027

JET SKI® SX-R™ 160

Kawasaki

Let the Good Times Roll®

 LIME GREEN/EBONY



POWER		PERFORMANCE	
Engine	4-stroke, DOHC, four valves per cylinder, 4-cylinder inline	Lubrication	Semi-dry sump system
Displacement	1,498cc	Coupling	Direct drive from engine
Bore x Stroke	83.0 x 69.2mm	Oil Capacity	5.3 qt
Compression Ratio	10.6:1	Fuel Capacity	6.1 gal
Induction	Naturally aspirated	Storage Capacity	N/A
Maximum Boost	N/A	DETAILS	
Cooling System	Inducted water	Overall Length	104.5 in
Fuel System	DFI® with 60mm throttle body	Overall Width	30.1 in
Ignition	TCBI with Digital Advance	Overall Height	33.1 in
Starting System	Electric	Estimated Dry Weight	TBA
Propulsion System	148mm jet pump, axial-flow, single stage	Curb Weight	TBA
Impeller	3-blade, oval-edge stainless steel	Seating Capacity	1
		Color Choices	Lime Green/Ebony

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied)

KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski® watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit puerto-rico.kawasaki-la.com for full product details.